

## Berrcom Non-contact Infrared Thermometer - 20000 in SA Stock, Mi



Product Name: Berrcom Non-contact Infrared Thermometer - 20000 in SA Stock, Mi

Manufacturer: -

Model Number: JOHCOVID001

Berrcom Non-contact Infrared Thermometer - 20000 in SA Stock, Min 5 units CE / ISO / FDA Approved with Certificates. Features: Measures Body Temperature, Surface Temperature, and Ambient Room Temperature without ever touching the object or person. Equipped with a 3-Color changing LCD screen, easily identify if an object or person is normal, medium or too hot. FAST AND SAFE - 1 second reading. Whether you're measuring a hot coffee, the coolness in your room on a hot summer day, or your child, you can do so without a hassle thanks to our quick and reliable thermometer. The thermometer also has a built in high temperature alarm that sounds once a fever is detected. The backlight will turn red and a sound will be made to alert you of a high fever. MOST RECORDINGS - No need to write down the last recorded temperature during a fever. This thermometer has built-in memory which can record up to 32 readings taken at anytime. Temperature can easily be taken in Fahrenheit or Celsius, with the push of a Unit button. Other thermometers are tricky to use and often times don't convert properly. RANGE + RELIABLE ACCURACY - Certified to be the most accurate reading thermometer in the market ( $\pm 0.3^{\circ}\text{C}$ ). With infrared technology you can rely on it when you need to the most. Easily take body temperature at a distance of 3-5 cm from the forehead, and objects as well. The body temperature range is  $32^{\circ}\text{C} \sim 42.9^{\circ}\text{C}$  / Surface Temperature is  $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$  Specifications: Model: JXB-178 Ambient temperature:  $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$  ( $50^{\circ}\text{F} \sim 104^{\circ}\text{F}$ ) Relative humidity:  $\leq 85\%$  Power: DC 3V (2pcs AA batteries) Unit size: 155 x 100 x 40 mm Unit weight: 125g Display Resolution:  $0.1^{\circ}\text{C}$  ( $0.1^{\circ}\text{F}$ ) In body mode:  $32^{\circ}\text{C} \sim 42.9^{\circ}\text{C}$  ( $89.6^{\circ}\text{F} \sim 109.2^{\circ}\text{F}$ ) In Surface Temp mode:  $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$  ( $32^{\circ}\text{F} \sim 140^{\circ}\text{F}$ ) Consumption:  $\leq 150\text{mW}$   $32.0^{\circ}\text{C} \sim 35.9^{\circ}\text{C}$  ( $89.6^{\circ}\text{F} \sim 96.6^{\circ}\text{F}$ ) :  $\pm 0.3^{\circ}\text{C}$  ( $\pm 0.6^{\circ}\text{F}$ ).  $36.0^{\circ}\text{C} \sim 39.0^{\circ}\text{C}$  ( $96.8^{\circ}\text{F} \sim 102.2^{\circ}\text{F}$ ) :  $\pm 0.2^{\circ}\text{C}$  ( $\pm 0.4^{\circ}\text{F}$ )  $39.1^{\circ}\text{C} \sim 42.9^{\circ}\text{C}$  ( $102.4^{\circ}\text{F} \sim 109.2^{\circ}\text{F}$ ) :  $\pm 0.3^{\circ}\text{C}$  ( $\pm 0.6^{\circ}\text{F}$ ) Measuring distance: 3 cm  $\sim$  5 cm (1.2 in  $\sim$  2 in) Automatic power-off: 30secs

**Price: R899.00**

Availability: This product was added to our catalog on Saturday 02 May, 2020